


NTN BEARING CORPORATION OF AMERICA

Head Office

1600 E. Bishop Court, P.O. Box 7604

Mount Prospect, IL 60056-7604, U.S.A.

Phone: 847-298-7500

Fax: 847-699-9744

Toll Free: 800-323-2358

Email: mkt@ntnamerica.com
Website: www.ntnamericas.com


Item # UCFL208D1, Two Bolt Rhombus Flanged Unit, Cast Housing, Set Screw, UCFL Type


[Order Now](#) | [Technical Specifications](#) | [Dimensional Specifications](#) | [Specifications](#)
Order Now
Ordering Options
FIND A DISTRIBUTOR
CONTACT NTN CUSTOMER SUPPORT SPECIALIST
ORDER THROUGH NTN DOL (AUTHORIZED DISTRIBUTORS ONLY)
Technical Specifications

Type	2-Bolt Rhombus Flanged Unit
Bearing Type	Ball Bearing
Locking Device	Set Screw

Seal Type	Contact
Seal Material	Nitrile Rubber
Bearing Number	UC208D1
Housing Number	FL208D1
Housing Material	Cast Iron
Housing Construction	1 Piece
End Type	Open
Performance	Light Duty
Dynamic Load Rating	6542 lbf 29100 N 29.10 kN
Static Load Rating	4002 lbf 17800 N 17.80 kN
Rotational Speed [Max]	3700 RPM
Weight	1.510 lb 0.680 kg
Operating Temperature Range	-40 to 250 °F -40 to 120 °C
Lubrication	Outer Ring Relubricatable

Dimensional Specifications



Two Bolt Rhombus Flanged Unit, Cast Housing, Set Screw, UCFL Type - Dimensions

d	1.5750 in 40.000 mm
H	6.8750 in 175.0 mm
L	3.9375 in 100.0 mm
J	5.6719 in 144.0 mm
A	1.4062 in 36.0 mm
A0	2.0156 in 51.200 mm
A1	0.5937 in 15.0 mm
A2	0.8281 in 21.0 mm
N	0.6250 in 16.0 mm
B	1.9370 in 49.200 mm
S	0.7480 in 19.000 mm
F	0.1772 in 4.500 mm

Specifications

Lubrication	Outer Ring
Ball Material	Through Hardened
Bore Type	Cylindrical
Outside Ring Width	0.8270 in 21.000 mm

Inside Ring Width	1.9370 in 49.200 mm
Clearance	CN
Cage Material	Pressed Steel
Precision Rating	ISO Class 0
Radial Dynamic Load Rating	6542 lbf 29100 N
Radial Static Load Rating	4002 lbf 17800 N
Rotational Speed [Max]-Grease	3700 RPM